

## REMARKS

Applicants have cancelled the original specification and substituted a Substitute Specification herewith to improve the form of the specification for examination.

Applicants have replaced original claims 1-3 with new claims 4-23 prior to calculation of the filing fee, to delete multiple dependency in the claims and improve the claims for examination.

Entry of the present amendments, prior to calculation of the filing fee, and examination of the above-identified application in due course, are respectfully requested.

To the extent necessary, Applicants petition for an extension of time under 37 CFR §1.136. Please charge any shortage in the fees due in connection with the filing of this paper, including extension of time fees, to Deposit Account No. 01-2135 (Case No. 612.44329X00) and please credit any excess fees to such deposit account.

Respectfully submitted,

  
\_\_\_\_\_  
Donald E. Stout

Registration No. 26,422

ANTONELLI, TERRY, STOUT & KRAUS, LLP

DES/kmh

Attachments

BACKGROUND OF THE INVENTION~~FIELD OF THE INVENTION~~ Field of the Invention

The present invention relates to a method of evaluating a capillary pressure curve of the rocks of an underground reservoir from measurements on rock debris taken therefrom.

~~BAKGROUND OF THE INVENTION~~ Description of the Prior Art

Laboratory measurements on cores or cuttings

Measurement of petrophysical parameters such as the permeability, the porosity and the capillary properties on rock fragments obtained while drilling a well through an underground formation is an interesting opportunity for operator companies to rapidly obtain a first petrophysical characterization of producing zones traversed by the well.

French Patent FR-2,809,821, filed by the applicant-assignee, describes a system of evaluating physical parameters such as the absolute permeability of porous rocks of an underground reservoir zone, from cuttings returned to the surface in the drilling mud. In an enclosure where the cuttings are dipped in a viscous fluid, some of this fluid is injected at a pressure that increases with time until a predetermined pressure threshold is reached, so as to compress the gas trapped in the pores of the rock. This injection stage is followed by a relaxation stage where injection is stopped. The pressure evolution during the injection process ~~being~~ is modelled from initial values selected for the physical parameters of the cuttings, ~~a~~ A computer adjusts ~~them~~ the values iteratively so as to obtain the best possible agreement between the modelled pressure curve and the pressure curve really measured.

BEST AVAILABLE COPY

French Patent—patent application FR-02/0023, filed by the applicant—assignee, describes another method of evaluating physical parameters such as the absolute permeability and the porosity of the rocks of an underground reservoir zone, also from cuttings. An enclosure containing the rock fragments and filled with a viscous fluid is communicated—communicates with a vessel containing the same fluid at a predetermined pressure so as to compress the gas trapped in the pores of the rock. The time of application of this pressure, according to whether it is short or long, allows to—measure measuring either of the pressure variation in the enclosure or the variation of the volume actually absorbed by the rock fragments. The pressure or volume evolution in the enclosure is then modelled from initial values selected for the physical parameters of the fragments, and the values of the physical parameters of the rock fragments are iteratively adjusted so that the modelled evolution best adjusts to the measured evolution of the physical parameter in the enclosure.

In the sphere—field of petrophysical—characterization study, the capillary pressure is also a very important datum for operators because it conditions :

- the initial distribution of the fluids in the reservoir from the aquifer zone (referred to as WOC, for water-oil contact, by the—man—those skilled in the art) to the upper part of the reservoir (transition zone). According to the capillary pressure curve associated with a reservoir rock and the nature of the fluids in place, this transition zone can extend over some—many meters or—some—ten—meters, which has an important effect on the determination of the accumulations in place,
- the input pressure of a rock, which is particularly important for cap rocks. For example, for a gas storage tank, the input pressure of the cap rocks conditions directly the allowable overpressure in the storage levels without having leaks.

With the current techniques, the capillary pressure curve is obtained by means of laboratory measurements on reservoir cores. These methods are expensive because of the coring operations as well as the measurements on the cores, and the results are often available only several months after drilling.

#### 5      *Approaches to rapidly obtain the capillary pressure curve*

However, there are alternative methods described in the literature for evaluating the capillary pressure curve rapidly, either during drilling or slightly later.

The most commonly used approach ~~consists in using~~ uses the mercury porosimetry technique for measuring the air/mercury capillary pressure curve  $P_c$  directly from cuttings. However, the obtained curve ~~obtained~~ is significantly different from the reference curve obtained ~~on~~ from cores with high wetting fluid saturations. ~~Besides~~ Further, this approach is based on the use of mercury, which is extremely polluting and progressively forbidden by the law in many countries, which poses a major problem for applying this technique in the near future.

15      Another known method uses the Nuclear Magnetic Resonance (NMR) technique to rapidly estimate the capillary pressure curve from stratigraphic data measured in the well shortly after drilling. It is notably described in the following publications :

- Bowers, M., A. et al. : ~~« Prediction of permeability from capillary pressure curves derived with NMR »~~ “Prediction Of Permeability From Capillary Pressure Curves Derived With NMR”, 17 September 1998,
- 20      - Marshall, D., et al. : ~~« Method for correlating NMR relaxometry and mercury injection data »~~ “Method For Correlating NMR Relaxometry And Mercury Injection Data”, SCA No. Society of Core Analysts International Symposium 1995,

- Volokitin, Y., W. J. et al. : «~~A practical approach to obtain 1<sup>st</sup> drainage capillary pressure curves from NMR core and log data~~» “A Practical Approach To Obtain 1<sup>st</sup> Drainage Capillary Pressure Curves From NMR Core and Log Data”, SCA No. Society of Core Analysts International Symposium 1999.

5        The NMR relaxation signal is first converted in terms of pore size distribution, then in terms of threshold size distribution, which allows ~~to calculate~~ calculation of a pseudo-capillary pressure curve. This approach has been tested on several samples of known curve  $P_c$ . The results show that a good agreement with the reference curves can only be obtained by means of a rigorous calibration stage to be carried out case by case

10       according to the nature of the rocks studied. This calibration stage is necessary owing to the uncertainty on :

- the NMR signal-pore size distribution conversion which depends on the value of the surface relaxivity which is variable according to the rocks, and
  - the pore size distribution-threshold size distribution conversion which depends on
- 15       the nature of the rock and on the diagenesis process.

      This approach is therefore not recommended in a predictive exploration context. In any case, it would not be applicable to cuttings.

      Image analysis has also been the subject of work intended to obtain a curve  $P_c$ . The porous medium is first prepared in a form of a thin section photographed by a scanning

20       electron microscopy or SEM. The image obtained is then ~~analysed~~ analyzed so as to determine parameters representative of the proportion and of the shape of the voids in relation to the rock. In particular, it is possible to determine a threshold size distribution to reconstruct a pseudo-capillary pressure curve  $P_c$ . The main limitation of this method

is the two-dimensional (2D) nature of the thin section, whereas the capillary pressure is by definition a three-dimensional (3D) property. Besides, this technique requires quite heavy conditioning, which is not really compatible with a result obtained slightly later. Image analysis could be applicable ~~on~~ to cuttings but it would require careful calibration  
 5 to acquire a good predictability.

Finally, it can be noted that the centrifuging technique is sometimes applied in the field to cuttings, ~~but in order~~ in order to extract the largest possible amount of drilling fluid from the rock to minimize pollutant discharges to the environment and to limit the cost by recycling the drilling fluid recovered. ~~As far as we know, no~~ The inventors do  
 10 not know of centrifugation ~~on~~ of cuttings ~~has~~ having been considered in order to determine capillary properties.

## SUMMARY OF THE INVENTION

The method according to the invention allows ~~to determine~~ determination of the capillary pressure curve of rocks of an underground reservoir from measurements on  
 15 rock debris or fragments (such as cuttings) taken therefrom, over the total saturation range of these rocks, within a short period and at a low cost, from these measurements. It comprises :

- measuring the permeability  $k$  of the rock debris;
- measuring the capillary pressure curve  $P_c$  as a function of the saturation of the rock  
 20 debris initially saturated with a fluid by subjecting them to centrifugation; and
- parametrizing a capillary pressure curve  $P_c$  satisfying empirical relations depending on adjustable parameters, that is constrained to adjust to an asymptotic part of the

capillary curve measured by centrifugation, and to the value of permeability  $k$  measured on the cuttings, so as to obtain ~~the a whole of the~~ capillary pressure curve.

Parametrizing the curve is advantageously carried out by selecting by default a set of ~~said the~~ parameters allowing calibration on the asymptotic part of the capillary pressure  $P_c$  with low saturations, and by modifying the parameters step by step so that the estimation of the permeability given by one of the empirical relations used is best adjusted with the measurements of permeability  $k$  carried out on rock debris ~~and with this the~~ asymptotic part.

Permeability  $k$  of the cuttings is measured for example from measurements of the pressure variations in a vessel filled with a fluid containing the cuttings after it has been ~~communicated coupled~~ for a predetermined period of time with a tank containing the same fluid under pressure, and from the volume actually absorbed by the cuttings, and from modelling the evolution of the pressure or of the volume in the vessel, from initial values selected for the physical parameters of the cuttings, which are iteratively adjusted so that the modelled pressure evolution best adjusts with the measured evolution of the physical parameters of the cuttings.

The method is notably advantageous in that it provides the capillary pressure of the rocks on the basis of simple cuttings that are more readily available and less expensive to obtain. The results are also obtained much more rapidly than with cores.

20      ~~BRIEF DESCRIPTION OF THE FIGURES~~ BRIEF DESCRIPTION OF THE  
DRAWINGS

Other features and advantages of the method according to the invention will be clear from reading the description hereafter of an embodiment given by way of non limitative example, with reference to the accompanying drawings wherein :

- ~~Figure Fig. 1~~ shows the evolution of the NMR signal during various centrifugation stages carried out on cuttings;  
5
- ~~Figure 2a-Fig. 2A~~ shows the curves  $P_c$  obtained on a single rock (B7) from cuttings and from a core;  
10
- ~~Figure 2b-Fig. 2B~~ shows the comparison between the reference curve  $P_c$  measured on a core and the reconstructed curve  $P_c$  over the total saturation range from the centrifugation measurements and the permeability measurement;  
15
- ~~Figures 3a and 3b-Figs. 3A and 3B~~ show results comparable to those shown in ~~Figs. 2a and 2b-Figs. 2A and 2B~~ respectively for another rock GDV1;  
20
- ~~Figures 4a and 4b-Figs. 4A and 4B~~ show results comparable to those shown in ~~Figs. 2a and 2b-Figs. 2A and 2B~~ respectively for another rock Rot1;  
25
- ~~Figures 5a and 5b-Figs. 5A and 5B~~ show results comparable to those shown in ~~Figs. 2a and 2b-Figs. 2A and 2B~~ respectively for another rock St Max;  
30
- ~~Figure Fig. 6~~ shows the comparison between the reference permeabilities and the permeabilities measured on cuttings within the scope of the method described in the aforementioned French patent application FR-02/0023; and  
35
- ~~Figure Fig. 7~~ diagrammatically shows the flowchart for implementing the method.  
40

#### DETAILED DESCRIPTION DETAILED DESCRIPTION OF THE INVENTION



The method intended for fast evaluation of a capillary pressure curve  $P_c$  from rock fragments or cuttings according to the invention is illustrated by ~~Figure-Fig.~~ 7. The method is based on two experimental measuring stages, followed by a parametrizing stage by reference with known curves, to reconstruct curve  $P_c$  over the total saturation range. During one of the measuring stages, capillary pressure data  $P_c$  are acquired by centrifuging the initially water-saturated rock fragments. The other experimental stage allows ~~to calculate~~ calculation of the permeability value  $k$  of the rock from the method described in the aforementioned French patent application FR-02/0023. Reconstruction of curve  $P_c$  over the total saturation range is carried out by using a parametrized form.

10 The parameters of the curve are determined in such a way that the curve matches the capillary pressure data  $P_c$  obtained experimentally and the estimated permeability value from the curve  $P_c$  obtained according to a known method such as Thomeer's or Swanson-Kamath's method, which are ~~reminded~~ described below, with the value measured on the rock fragments. Several application cases are presented, with show the

15 very good agreement obtained with reference curves without any particular previous calibration procedure.

#### **I) Measurement of $P_c$ by centrifugation from the cuttings**

To implement the method, it is possible to use standard centrifugation means or more sophisticated means with automatic monitoring of the volumes of fluid produced, such as those described for example in patents EP-603,040 (US-Patent 5,463,894), FR-French patents 2,763,690, FR-2,772,477 (US- patent 6,185,985) or FR 2,798,734 filed by the ~~applicant~~ assignee.

20

The cuttings which have come up to the surface during the drilling operation are first cleaned with solvents in a Soxhlet type device, then dried and saturated with 30 g/l

brine. The cuttings are then drained in a damp cloth so as to remove the water trapped between the various cuttings d, then placed in a cell or cup fastened to the end of a rotating arm. The water expelled by centrifugation from the cuttings flows through a grate and it is collected at the base of the cup. The experimental data are acquired in the same way as in the context of centrifugation on a core. For a centrifugation stage (given rotating speed), the evolution of the water production is measured until no significant variation can be observed any longer, then the rotating speed is increased to start a new stage.

As can be seen in ~~Figure~~ Fig. 1, a progressive decrease of the NMR signal and a shift to the short relaxation times  $T_2$  are observed, which express a desaturation of the porous medium with the increase of the rotating speed. This type of measurement shows that there definitely is a capillary contact between the cuttings, which allows to measure  $P_c$  by centrifugation from cuttings.

The volume of water produced during the experiment is converted to saturation data from the volume of water initially contained in the cuttings. The latter is determined by weighing (difference in the weight of the cuttings before and after saturation) or directly by NMR measurement.

~~Figures 2a to 5a~~ Figs. 2A to 5A show the result of experiments carried out from model cuttings, 1 to 2 mm in size, manufactured in the laboratory from rocks of known properties for which a curve  $P_c$  conventionally measured by centrifugation of a core is available. It can be seen that a good agreement is obtained with the reference curve at the level of the asymptotic part (low wetting fluid saturation). On the other hand, a big difference is observed for higher wetting fluid saturations. Results equivalent to those

obtained within the context of porosimetry measurements using mercury on cuttings are thus obtained, without pollution risks.

The measured capillary pressure curve  $P_c$  is however representative only on the asymptotic part. A reconstruction procedure is therefore necessary to evaluate the  
 5 ~~behaviour~~behavior of the curve over the total saturation range.

## II) Measurement of the permeability $k$ of the cuttings

The method described in the aforementioned French patent application 02/02,242 is applied to measure the permeability of the cuttings. The cuttings are therefore dipped in a containment enclosure containing a viscous fluid. The enclosure is then  
 10 ~~communicated with~~coupled to a vessel containing the same fluid under pressure, so as to compress the gas trapped in the pores of the rock. According to a first embodiment, this communication period can be very short and followed, after a latency time, by the measurement of the pressure evolution in the enclosure. According to another embodiment, the communication period can be long enough to allow ~~to observe~~  
 15 observing and measure~~measurement of~~ the variation of the volume actually absorbed by the cuttings.

The evolution of the pressure or of the volume in the enclosure is then modelled from initial values selected for the physical parameters of the cuttings, and the values of the physical parameters of the cuttings are iteratively adjusted so that the modelled  
 20 evolution best adjusts with the measured evolution of the physical parameter in the enclosure.

This procedure gives excellent results. The permeability values  $k$  of the cuttings are totally in accordance with the reference measurements obtained from cores.

### III) Reconstruction of the total capillary pressure curve

In this third stage, ~~we synthesize the previous measurements~~ are synthesized that have allowed to ~~construct~~ construction of the asymptotic part of the capillary pressure curve  $P_c$  and the measurements of permeability  $k$  using empirical relations ~~reputed to~~ model as well the physical parameters of rocks ~~well~~. The following publications :

- Thomeer, J.H.M. : “~~Introduction of a pore geometrical factor defined by the capillary pressure curve~~Of A Pore Geometrical Factor Defined By The Capillary Pressure Curve”, Trans AIME, vol. March, pp.73-77, 1960, and
- Thomeer, J.H.M. : “~~Air permeability as a function of three pore network parameters~~Permeability As A Function Of Three Pore Network Parameters”, Trans AIME, vol. April, pp.809-814, 1983

describe methods for evaluating the permeability from a capillary pressure curve. A Capillary capillary pressure curve  $P_c$  is modelled in the following form :

$$P_c = P_d \times \exp\left(-\frac{G}{\ln\left(\frac{V_b(P_c)}{V_b(P_\infty)}\right)}\right)$$

where :

- $G$  is a shape parameter for ~~taking account of~~ accounting for the curvature of the capillary pressure curve (related to the shape of the pore size distribution);
- $P_d$  is the displacement pressure extrapolated to  $S_{Hg}$  equal to zero; and
- $V_{b\infty}$  is the percentage of volume occupied by the mercury at the end of the experiment at an infinite capillary pressure (equal to  $\phi \times S_{Hg}$ );

The three parameters of the model being related to the permeability by the following expression :

$$k = 3.8068 \times G^{-1.334} \times \left[ \frac{V_{hso}}{P_d} \right]^2.$$

In the following publication :

- 5 - Swanson, B.F. : “~~A simple correlation between permeability and mercury capillary pressures~~Simple Correlation Between Permeability And Mercury Capillary Pressures”, JPT, vol. December, pp.2498-2504, 1981,

the author proposes correlating the value of the permeability with the maximum value of ratio ( $V_b/P_c$ ) on the mercury porosimetry curve. This particular point generally  
10 corresponds to the regime change that occurs at the end of the percolation regime, just before the significant capillary pressure increase. As regards the capacity of fluid flow in the porous medium, this point is particularly important because it represents the pore size for which the entire pore network is connected and which therefore controls the flow. The most general correlation provided by the author is given by the expression  
15 (Swanson 1981) :

$$k = 355 \times \left( \frac{V_b}{P_c} \right)_A^{2.005}$$

The following publication :

- Kamath, J. : “~~Evaluation of accuracy of estimating air permeability from mercury injection data~~Of Accuracy Of Estimating Air Permeability From Mercury Injection  
20 Data”, SPE Formation evaluation, vol.7,4, pp.304-310, 1992

also relates to the comparative evaluation of the approaches using empirical correlation or physical models to determine the permeability value from a mercury porosimetry curve. The best agreement is obtained with a new correlation based on the aforementioned characteristic length by Swanson 1981, mentioned above :

$$5 \quad \begin{aligned} k &= 413 \times L_{\max}^{1.85} & \text{if } k < 1mD \\ k &= 347 \times L_{\max}^{1.60} & \text{if } k > 1mD, \end{aligned}$$

$L_{\max}$  being defined as follows :

$$L_{\max} = \left( \frac{\phi \times S_{mv}}{P_c} \right)_{\max} = \frac{\phi \times \lambda \times (100 - S_r)}{P_e \times (1 + \lambda)^{\frac{1}{\lambda} + 1}} \quad \text{and} \quad \left( \frac{P_e}{P_c} \right)^{\lambda} = \frac{S_w - S_r}{100 - S_r}$$

where :

- $\lambda$  : exponent expressing the curvature of the capillary pressure curve (related to the shape of the pore size distribution),
- $P_e$  : the displacement pressure extrapolated to  $S_{Hg}$  equal to zero, and
- $S_r$  : residual saturation occupied by the wetting fluid (%).

To parametrize the empirical capillary pressure curve  $P_c$  obtained from Thomeer's, Swanson's or Kamath's approaches, it is constrained to adjust to the asymptotic part obtained by centrifugation during the first stage of the method. The entire curve is constrained using also the value of permeability  $k$  measured on cuttings during the second stage of the method, which is compared with the result of the empirical relations. The parameters of the capillary pressure  $P_c$  are then modified until both the measured asymptotic ~~behaviour~~ behavior and the permeability estimation are met, which allows to ~~constrain~~ constraining the capillary pressure curve over the total saturation range  $S_w$ .

The inversion process starts with a set of default parameters which allow to ~~calibrate~~ calibration of the asymptotic behaviour ~~behaviour~~ of the capillary pressure  $P_c$  with low water saturations. These parameters are then modified step by step (mainly the input pressure  $P_e$  or  $P_d$  and the shape factor  $\lambda$  or  $G$ ) so that the estimation of the permeability given by one of the previous relations is in good agreement with the permeability measurement obtained on cuttings while keeping a good agreement with the measurements of  $P_c$  at low water saturations.

### 1.1 Results obtained

Figures ~~2b, 3b, 4b and 5b~~ 2B, 3B, 4B and 5B show the comparison between the curve  $P_c$  reconstructed according to the previous procedure and the reference curve  $P_c$  obtained on a core. It can be seen that, whatever the example considered, the reconstruction method allows to ~~obtain~~ obtaining a pertinent evolution of  $P_c$  over the total saturation range and in particular at high water saturations, whatever the permeability of the rock.

Name	K (mD)	G	Vb (fraction)	Pe (bar)
Rot1	150	0.28	0.89	0.38
GDV1	195	0.28	1.00	0.41
B7	780	0.25	0.92	0.2
StMax	2000	0.34	0.92	0.26

PATENT

INSTITUT FRANÇAIS DU PETROLE

**METHOD OF EVALUATING THE CAPILLARY PRESSURE CURVE  
OF ROCKS OF AN UNDERGROUND RESERVOIR  
FROM MEASUREMENTS ON DEBRIS**

Inventors : Roland LENORMAND, Patrick EGERMANN and Daniel LONGERON

ABSTRACT

~~Method~~ A method of evaluating the capillary pressure curve of rocks of an underground reservoir from measurements on rock debris or fragments such as cuttings from the reservoir, over the total saturation range of these rocks, within a short period and at a low cost, from these measurements is disclosed. The method

~~It essentially comprises~~ measuring the permeability  $k$  of the debris, measuring the capillary pressure curve  $P_c$  as a function of the saturation of these fragments initially saturated with a fluid (brine for example) by subjecting them to centrifugation, and parametrizing a capillary pressure curve  $P_c$  satisfying empirical relations depending on adjustable parameters, constrained to adjust to an asymptotic part of the capillary curve measured by centrifugation, and to the value of permeability  $k$  measured on the cuttings, so as to obtain the whole of the capillary pressure curve.

- Applications ~~÷ include~~ hydrocarbon reservoir evaluation ~~for example.~~



**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**